

Dahua Technology Entry IPC-HFW1239S1-A-IL Bala (forma) Cámara de seguridad IP Interior y exterior 1920 x 1080 Pixeles Techo/pared/Tubo

Marca: Dahua Technology Familia de productos: Entry Código del producto: DH-IPC-HFW1239S1-A-IL

Nombre del producto: IPC-

HFW1239S1-A-IL

Dahua Technology Entry IPC-HFW1239S1-A-IL. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.0005 Lux, Ángulo de rotación: 360°, Ángulo de inclinación: 0 - 90°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"), Número de píxeles efectivos (A x V): 1920 x 1080 Pixeles. Distancia de visión nocturna: 30 m

Performance		Video	
Type * Placement supported * Connectivity technology * Wide Dynamic Range (WDR)	IP security camera Indoor & outdoor Wired	Digital Wide Dynamic Range (DWDR) Region of Interest (ROI) encoding Smart IR	<i>*</i>
Day/night mode	v		•
, ,	v	Audio	
Built-in light	CE-LVD: EN62368-1 CE-EMC:	Signal-to-Noise Ratio (SNR)	56 dB
Certification	2014/30/EU	Built-in microphone	✓ C 711M:: C 711a C 726 DCM
Design		Voice codecs	G.711Mu, G.711a, G.726, PCM
Form factor *	Bullet	Network	
Mounting type * Product colour * Housing material International Protection (IP) code	Ceiling/Wall/Pole White Metal, Plastic IP67	Ethernet LAN * Ethernet interface type Networking standards	Fast Ethernet IEEE 802.3af IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; SMTP; FTP; DHCP;
Camera		Supported network protocols	DNS; DDNS; NTP; Multicast; ICMP; IGMP
Minimum illumination Angle of rotation Tilt angle range	0.0005 lx 360° 0 - 90°	Wi-Fi * Bluetooth * Number of users	x x
Pan range	0 - 360°		6 user(s)
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Storage	
Camera shutter type	Electronic	Built-in HDD *	X
Camera shutter speed	1/3 - 1/100000 s	ROM capacity RAM capacity	16 MB 64 MB
Number of Privacy masking areas	4	, ,	04 MB
Image sensor		Ports & interfaces	1
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Ethernet LAN (RJ-45) ports	1
Progressive scan	✓	Security	
Sensor type *	CMOS	Video motion detection	✓
Number of effective pixels (H x V)	1920 x 1080 pixels	Mirror	✓
Lens system		Management features	
Number of lenses *	1	Web-based management	✓
Night vision		Management software	Smart PSS Lite; DSS; DMSS; DoLynk
Night vision *	✓	_	Care
Night vision distance	30 m	Power	
Number of illumination LEDs	1	Power consumption (typical)	DC, PoE
Video		Power consumption (typical) Power consumption (max)	1.4 W 3.3 W
Maximum resolution * Total megapixels *	1920 x 1080 pixels 2 MP	Power consumption (Power over Ethernet (PoE))	4.4 W

Video		Power		
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+, M-JPEG 1280 x 960, 352 x 288, 352 x 240, 640 x 480 (VGA), 1920 x 1080 (HD 1080), 1280 x 720 (HD 720), 704 x 576, 704 x 480	DC output voltage	12	
		Operational conditions		
Supported graphics resolutions		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 60 °C -40 - 60 °C 0 - 95%	
Supported video modes	720p, 1080p		5 55 %	
Frame rate	30 fps	System requirements		
Video streaming	✓	Mobile operating systems supported Android, iOS		
Noise reduction	✓	Weight & dimensions		
Noise reduction technology	3D noise reduction	Width	70 mm	
Gain control type	Auto/Manual	Depth	162.6 mm	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	ricigite	70 mm	
Bit rate	H.264: 32 kbps-4096 kbps; H.265: 12 kbps-4096 kbps	Weight	220 g	
		Packaging data		
Back Light Compensation (BLC)	✓	Package weight	350 g	
Highlight Compensation (HLC)	✓	Packaging content		
		Number of cameras *	1	

